

1/4" HOSE OPTIONS:

STANDARD FITTINGS:

PART#

- G60RBY-60" length 3Pack Red, Blue, Yellow
- G72RBY- 72" length 3Pack Red, Blue, Yellow
- G60Y- 60" length Single Yellow
- G72Y- 72" length Single Yellow



BALL VALVE FITTINGS:

PART#

- GBV60RBY- 60" length 3Pack Red, Blue, Yellow



ANTI-BLOWBACK FITTINGS:

PART#

- GAB48RBY- 48" length 3Pack Red, Blue, Yellow
- GAB60RBY-60" length 3Pack Red, Blue, Yellow
- GAB72RBY- 72" length 3Pack Red, Blue, Yellow
- GAB60Y- 60" length Single Yellow
- GAB72Y- 72" length Single Yellow



FEATURES: all hoses



- All assemblies and components are made in the USA
- Rated 800 PSI maximum working pressure / 4000 psi minimum burst pressure
- Nylon, veneer-lined hose for low permeation applications meeting EPA requirements
- Double-barrier design of black, polychloroprene rubber with braided aramid yarn for additional permeation protection and strength
- Quality brass fittings to ensure longer hose life and safety
- Approved for the following refrigerants: R12, R22, R134a, R410A, R414A, R500, R502, FR1GC-FR12, R11, R113, R114, R123, R401A, R401B, R402A, R402B, R404A, R407A, R407B, R407C, R408A, R409A, R507, R32, R454B

FEATURES: continued

ANTI-BLOW BACK HOSES:

- Low-loss fittings that immediately trap refrigerant eliminating venting and finger burns
- Super-neoprene gaskets have longer-life with slower deterioration
- Knurled nut designed for better grab for tightening in harder to reach places-

BALL VALVE HOSES:

- Full flow, in-line ball valve
- 8" length of hose between ball valve and fitting for easy accessibility

SPECIFICATIONS:

CONSTRUCTION:

Tube Veneer: Nylon

Tube Tie Gum: Black polychloroprene rubber

Braid: Braided (1) aramid yarn

Cover: Nitrile/PVC rubber, RMA Class B (medium oil resistance), ozone resistant.

TEMPERATURE: -22 °F to +203 °F

WEIGHT: 6.9 lbs per 100 ft of hose

DIMENSIONS AND PRESSURE RATINGS:

ID inch	OD inch	WP PSI	Burst PSI
0.226 +/- 0.015	0.450 +/- 0.020	800	4000

Meets Industry Standards: UL1963, SAE 2196, SAE J2888

MANIFOLDS:

PART#

-R3M4G- Refrigerant type R22, R404A, R410A

-R3M2G- Refrigerant type R134A, R404A, R22

- All assemblies and components made in USA
- Forged brass body with metal valve handles
- Heavy-duty swivel hook
- Vibration free gauges for minimal needle movement



Goss Inc.
1511 Route 8
Glenshaw, PA 15116

GOSS 
HVAC Tools & Equipment

Phone: 800-367-4677
www.gossonline.com